C-LAB.Ltd
17 HaYetsira Street, Moradot HaCarmel
Industrial Park,Yokneam Ilit, Israel,
2069208
Fax: 972 4 8325251, Tel: 972 4 8290100
www.compulab.co.il

Standard HW Reliability Prediction Report

Methodology: EN/IEC 61709 (SN 29500)	Standard HW reliability Prediction Report		
Product: FITLET3-CX6425-S-A-D16-N256-FLAN-TI-PN-TPM			
***Reliability**: EN/IEC 61709 (SN 29500)	MTTF, h	γ	FIT
	1.43E+05	6.99E+00	6.99E+03
Product: FITLET3			
Reliability based on RMA statistics	MTTF, h		
	2.4E+06		

The results are valid under following conditions:
SNA: Nonmobile operation ground benign;
T ambient - mean component ambient temperature according to the next temperature ranges :
Industrial Certified -40°C to 85°C;
Load: Continuous operation 8760 h per year.

Notes:
1) FIT, failure rate per 10^9 component hours
2) γ, failure rate per 10^6 component hours
3) Reliability values are valid for temperature range selected by Customer at product order.
4) MTTF, Mean Time To Failure

*SSD Reliability depends on data pattern AND/OR SSD volume utilization by customer application and may differ from provided by SSD Manufacturer.